

### Amendments to the Claims

1. (currently amended) A system for coupling a heat sink to an electrical device having one or more components independently of a clamping member that is used to place a coupling force between one or more electrical devices and a substrate to which the one or more electrical devices are to be electrically connected, the system comprising:

a clamping member for providing a compressive force on ~~adapted to push the one or more electrical devices, to push the one or more electrical devices against the substrate, to assist in electrical connection between the one or more electrical devices and the substrate,~~ the clamping member defining a through-hole leading to each electrical device, and further defining one or more relief volumes to prevent the clamping member from contacting a portion of a surface of the one or more electrical devices;

a heat-conducting member in ~~the~~ through-hole of the clamping member and adapted to thermally contact the electrical device to conduct heat into or out of the electrical device separately from the compressive force provided by the clamping member, where a lower surface of the heat-conducting member includes one or more relief volumes that prevent the heat-conducting member from contacting a portion of a surface ~~one or more components of the~~ electrical device;

a resilient member located within the clamping member through-hole in which the heat-conducting member is located, for urging the heat-conducting member into thermal contact with the electrical device; and

a heat sink in thermal contact with the heat-conducting member.

2. (original) The coupling system of claim 1 in which the heat-conducting member comprises a post with an enlarged end that contacts the electrical device.
3. (previously presented) The coupling system of claim 2 in which the through-hole in the clamping member in which the heat-conducting post is located defines a shoulder between the heat sink and the electrical device, the shoulder defining a through-hole width that is less than width of the enlarged end of the post, to allow the post to move within the through-hole yet prevent the post from being withdrawn from the through-hole.
4. (cancelled)
5. (previously presented) The coupling system of claim 1 in which the resilient member comprises a coil spring located around the heat-conducting member.
6. (previously presented) The coupling system of claim 1 in which one end of the resilient member contacts the heat-conducting member and the other end contacts the clamping member such that the resilient member is compressed when the clamping member is moved toward the substrate.
7. (original) The coupling system of claim 1 in which the heat-conducting member protrudes from the clamping member.
8. (original) The coupling system of claim 7 in which the heat sink is located outside of the clamping member.
9. (original) The coupling system of claim 8 in which the heat sink directly contacts the heat-conducting member.
10. (original) The coupling system of claim 7 in which the heat-conducting member and heat sink are integral.

11. (original) The coupling system of claim 1 in which the clamping member directly contacts the electrical device.

12. (original) The coupling system of claim 11 in which the clamping member directly contacts some but not all of the electrical device upper surface.

13. (currently amended) A system for coupling a heat sink to an electrical device having one or more components independently of a clamping member that is used to place a coupling force between one or more electrical devices and a substrate to which the one or more electrical devices are to be electrically connected, the system comprising:

a clamping member for providing a compressive force on ~~adapted to push the one or more electrical devices, to push the one or more electrical devices~~ against the substrate, ~~to assist in electrical connection between the one or more electrical devices and the substrate,~~ the clamping member defining a through-hole leading to each electrical device, and further defining one or more relief volumes to prevent the clamping member from contacting a portion of a surface of the one or more electrical devices;

a heat-conducting post in ~~the~~ through-hole of the clamping member with an enlarged end adapted to thermally contact the electrical device separately from the compressive force provided by the clamping member, to conduct heat into or out of the electrical device, where the enlarged end of the heat-conducting post includes one or more relief volumes that prevent the heat-conducting post from contacting a portion of a surface ~~one or more components of the electrical device;~~

a heat sink in thermal contact with the heat-conducting post; and

a spring in the through-hole in the clamping member adapted to be compressed between the clamping member and the enlarged end of the post, to assist in thermal contact between the enlarged end and the electrical device.

14. (original) The coupling system of claim 13 in which the spring comprises a coil spring located around the post.